

**DECLARATION OF PERFORMANCE according to EAD 220020-00-0402
 (According to Regulation CE mark of construction products N° 305/2011)**

N: DOP_I_43106_TEGOLA_CASTOR_V01.DOCX

1. Name and identification code: TEGOLA CASTOR – Code according to colour: 43111 Rojo Castilla / 43121 (Marrón Otoño) / 43106 (Negro Elegance) / 43116 (Verde Galicia).

2. Type: TEGOLA CASTOR. Lot: See label on the product

3. Manufacturer:

ASFALTOS CHOVA, S.A.
 Ctra. Tavernes a Liria, km 4,3. 46760 TAVERNES DE LA VALLDIGNA. Valencia
 E-mail: chova@chova.com – www.chova.com

4. Intended use/es:

Light asphalt shingle with mineral reinforcement (fiberglass).
For waterproofing pitched roofs with slope $\geq 15\%$ (bilayer) and $\geq 30\%$ (single-layer or bilayer).

5. System or systems for evaluation and verification of constancy of benefits:

System 4

6. Notified Body/ies:

Not applicable – System 4

7. Declared performances, evaluated according to indications:

EAD 220020-00-0402

8. Declared performances:

| TEST | METHOD | UNIT | VALUE | TOLERANCE |
|---------------------------|---------------------------|-------------------|------------|-----------|
| Weight (finished product) | - | Kg/m ² | 9,4 | - |
| Bitumen per single layer | EN 544 | g/m ² | >1000 | - |
| Tensile strength (L/T) | EN 544 | N/50mm | >600/>400 | - |
| Resis. to tearing | EN 544 | N | >100 | - |
| Water absorption | EN 544 | % | <1 | - |
| Resis. to UV radiation | EN 1297 | Visual | Pass | - |
| Resis. to blistering | EN 544 | Visual | Pass | - |
| Flow resistance (at 90°C) | EN 1110 | mm | <1 | - |
| Granules adhesion | EN 544 | g | <1,5 | - |
| External fire resistance | EN 13501-5/EN 1187 | - | Broof (t1) | - |
| Reaction to fire | EN 13501/prEN ISO 11925-2 | - | E | - |

The performance of the product identified in point 1 is in accordance with the performance declared in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer:



Name: D. Antonio Chova Félix
 ChovA, S.A.

Tavernes de la Vallidigna, September 15, 2022

ANNEX OF CE MARKING: TEGOLA CASTOR



Asfaltos Chova, S. A.
Ctra. Tavernes a Liria, km 4,3. 46760 Tavernes de la Valldigna. (Valencia)
España

20

DOP_I_43106_TEGOLA_CASTOR_V01.DOCX

EAD 220020-00-0402. System 4

TEGOLA CASTOR

Light asphalt shingle with mineral reinforcement (fiberglass).
For waterproofing pitched roofs with slope $\geq 15\%$ (bilayer) and $\geq 30\%$ (single-layer or bilayer).

| | |
|------------------------------------------------|------------|
| Weight (finished product) (kg/m ²) | 9,4 |
| Bitumen per single layer (g/m ²) | >1000 |
| Tensile strength (L/T) (N/50mm) | >600/>400 |
| Resis. to tearing (N) | >100 |
| Water absorption (%) | <1 |
| Resis. to UV radiation | Pass |
| Resis. to blistering | Pass |
| Flow resistance (at 90°C) | <1 |
| Granules adhesión (g) | <1,5 |
| External fire resistance | Broof (t1) |
| Reaction to fire | E |

Tavernes de la Valldigna, September 15, 2022