

COMPLETE INFORMATION OF CHOVAPLAST POL PY 30 SHEET



View "Declaración de Prestaciones – DoP" in: DoP_E_14009_13707_CHOVAPLASTPOLPY30_v01

View CE brand, complete, in: DoP_E_14009_13707_CHOVAPLASTPOLPY30_v01

ASFALTOS CHOVA, S.A.

Ctra. Tavernes a Liria, km 4,3. 46760 TAVERNES DE LA VALLDIGNA. Valencia

Sheet description:

Auxiliary sheet of 1 m x 12 m and 3 kg/m² of polymer additivated bitumen, with polyester nonwoven felt reinforcement, plastic interior and exterior trim. Place by adhesion with blowtorch. In "Adherents" or "No Adherents" systems.

Recommended for: According to regulations of the country of use.

Not recommended for: monolayer system, bilayer system only with auxiliary sheets; top sheet in bilayer system in the open; top sheet in landscape roof.

TEST	METHOD	VALUE	UNIT	TOLERANCE
External Fire Performance:	EN 13501-5 : 2002	B _{ROOF} (t1)		Documentation of A. Chova,,
Reaction to fire:	EN 13501-1 : 2002	Class E		verified by AENOR
Watertightness:	EN 1928 : 2000	Pass		
Tensile strength in:				
- longitudinal direction:	EN 12311-1 : 1999	600	N / 5 cm	± 200
- transverse direction:		400		± 150
Elongation:				
- longitudinal:	EN 12311-1 : 1999	35	%	± 15
- transverse:		35		± 15
Root resistance (penetration):	EN 13948 : 2007	PND		
Static loading resistance:	EN 12730 : 2001	PND		
Impact resistance:	EN 12691 : 2006	PND		
Tear resistance:	EN 12310-1 : 1999	--		
Joints strength: (to shear)	EN 12317-1 : 1999	--		
Durability:	EN 1296 : 1999			
	(Pliability)	EN 1109 : 1999	--	
	(Flow resistance)	EN 1110 : 1999	--	
Pliability:	EN 1109 : 1999	≤ -10	°C	
Dangerous substances:	--	PND		

Pass ⇨ Positive or correct; NPD ⇨ No Performance Declared; -- ⇨ Not required

OTHER ADDITIONAL FEATURES OF CHOVAPLAST POL PY 30 SHEET

Designation:	UNE 104410		LA-30-FP	
Visible defects:	EN 1850-1		No visible defects	
Mass per unit area:	EN 1849-1	3,0	kg/m ²	-5 / +10 %
Roll size: (Length x Width)	EN 1848-1	12 x 1	m	≥
Granule loss:	EN 12039	--	%	
Dimensional stability:	EN 1107-1	≤ 0,6	%	
Flow resistance:	EN 1110	≥ 70	°C	

Date: 1st December 2016



**Product with AENOR brand
(according UNE-EN 13707)**

Provided information corresponds to data obtained in our own laboratories. This product will maintain these characteristics on average. ChovA, S.A. reserves the right to modify or cancel any parameter without notice. ChovA, S.A guarantee is only applying to the product quality.

As for commissioning work, which do not participate, they must also meet the waterproofing requirements for the implementation, specified in the applied rules, both in membrane composition and fulfillment them.

This technical data sheet will be void by subsequent revisions and, if in doubt, apply the latest revision.