

# ChovASTAR COLOR WATERPROOFING

CHOVASTAR®

Red 1kg 75227 - 5kg 75220 - 20kg 75216

Grey 1kg 75226 - 5kg 75222 - 20kg 75218

White - 5kg 75221 - 20kg 75217

## Roof protection from dump and rain

### Description

ChovASTAR® COLOR WATERPROOFING is a dense acrylic based waterproofing product available in varios colors and sizes.

It is recommended to apply as visitable terraces exterior finish as a protection against dump and rain.



1kg  
5kg  
20kg

### Installation

Surface on apply must be clean and preferably lightly moist. The ambient temperature should be above 5 °C and be no likelihood of rain

Stir the product. Apply a first layer using a roller. It's recommended extending a reinforcing mesh over the first layer. Leave dry 4-6 hours and apply the second layer. Applying a third layer is recommended.



white

red

grey



In case of doubt about the installation, please contact our Technical Department.

 ChovA



Waterproofing solutions

Color waterproofing

## Roof protection from dump and rain

### Additional information

Presentation: Plastic container. Content 1 or 5 kg.

Performance: It is recommended apply 2 or 3 painting layers with a minimum advised yield of 400 a 500 g/m<sup>2</sup> per layer. With a 5 kg pot, 4-6 m<sup>2</sup> are covered and with 1 kg one, 1,25 m<sup>2</sup> are covered.

Cleaning: If product is fresh, tools used can be easily cleaned with water. Once dry, must clean using solvents.

Storage: Store it protected from weather, out of sun and temperatures above 5 °C.

### Technical Specifications

DRYING TIME BETWEEN LAYERS .....	4-6 hours
APPLICATION TEMPERATURE .....	5° C to 30° C
INFLAMMABILITY .....	NON-FLAMMABLE
COMBUSTIBILITY .....	NON-COMBUSTIBLE
DOES NOT CONTAIN SOLVENTS	
COLOR .....	RED, GREY AND WHITE



# ChovA



## Waterproofing solutions