

ChovASTAR® COLA AISLAMIENTOS

CÓD. 58100 - COLA AISLAMIENTOS 20 L.
 CÓD. 58301 - COLA AISLAMIENTOS 05 L.

Contact adhesive composed of polychloroprene modified with resins, of great versatility and high performance.



TECHNICAL SPECIFICATIONS

CHEMICAL BASE	Polychloroprene with resins
SOLIDS	22 ± 1%
VISCOSITY AT 25° (CPS)	3200 ± 300
OPEN TIME (minutes)	20-30
DRYING TIME (minutes)	8-10
CRYSTALIZATION SPEED	Medium-High
HEAT RESISTANCE	High
APROXIMATE PERFORMANCE (l/m ²)	0,5 (0,25 on each surface)

STORAGE: The material must be kept closed in a well-ventilated place between 5°C and 30°C, away from any flame or source of sparks. Shelf life of 1 year in the original container.

INSTALLATION

- 1- The surface and material to be installed must be clean and dry.
- 2- Apply the contact adhesive with a roller or brush, on both surfaces to be glued.
- 3- Lay dry for 8 to 10 minutes, until the adhesive is dry to the touch.
- 4- Place the material on the glued support, pressing hard to facilitate adhesion.
- 5- Don't smoke during the installation process or pour waste down the drain.
- 6- Use a protective mask to avoid inhalation.



RECOMMENDED FOR...

- Glue the support for the installation of multilayer materials **ChovACUSTIC**, **ChovAPREN** and other fibrous insulating materials.
- Supports: Construction materials, metals, ceramics, wood, carpets, fabric, paper and rubber.

Not recommended on flexible plastic supports, PP, PE and PTFE.