



ChovA
SISTEMAS DE IMPERMEABILIZACIÓN
Y AISLAMIENTO

PUNTAS Tegola Madera

GALVANIZED STEEL TOES

TECHNICAL FILE N° 84485 – REV. 1/20 – 11/09/2020

DESCRIPTION

Galvanized Steel toes with wide head for bituminous **Tegola Americana**, on wooden support.



DIMENSIONS

Head	Minimum diameter	9	mm
Body	Approximate diameter	3,9	mm
Length	Approximate	20	mm

CONSUMPTION

4 tips for each **Tegola Americana** placed plate is used, STANDARD model. Approximate 27-30 tips are used per m² placed.

6 tips for each **Tegola Americana** placed plate is used CASTOR model. Approximate 40-45 tips are used per m² placed.

For slopes higher than 100 % (45 °), is recommended to use 6 tips per each **Tegola Americana** plate, STANDARD model, that is 40 - 45 tips per m².

For slopes higher than 100 % (45 °), is recommended to use 10 tips per each **Tegola Americana** plate, CASTOR model, that is 68 - 72 tips per m².

WEIGHT AND YIELD

1 kg of tips contains between 375 and 425 units.

With 1 kg of tips can be placed between 13 and 15 m² **Tegola Americana** plate, STANDARD model, under normal conditions.

With 1 kg of tips can be placed between 9 and 10 m² **Tegola Americana** plate, CASTOR model under normal conditions.

Provided information matches up with data obtained in our own laboratories and/or accredited external laboratories. This product will maintain these characteristics on average. ChovA, S. A. reserves the right to modify or cancel any parameter without previous notice. ChovA, S. A. guarantee is limited to the product quality. As for commissioning work, which do not participate, the product installation instructions must be followed carefully. Soundproofing values may differ from those shown here due to improper execution of work. This technical file will be voided by subsequent revisions and, if in doubt, request the latest revision.